

(11) Publication number:

6

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **60084583**

(51) Intl. Cl.: H01L 21/30 H01L 21/68

(22) Application date: 22.04.85

(30) Priority:

(43) Date of application

publication:

30.10.86

(84) Designated contracting

states:

(71) Applicant: CANON INC

(72) Inventor: YAMADA YUICHI

OUTSUKA KAZUHITO

(74) Representative:

(54) CORRECTION OF ORIGIN DEVIATION BETWEEN STATIONARY STAGE AND ROTARY STAGE


(57) Abstract:


PURPOSE: To prevent a new deviation from occurring by correcting θ slip by a method wherein, when there is a deviation between the coordinate origin of rotary stage and the other coordinate origin of stationary stage, the deviation of origin is corrected.

CONSTITUTION: Assuming azimuth to be θ , a common point to a stationary stage and a rotary stage, the coordinate origin (rotary center) of rotary stage and the other coordinate origin of stationary stage are respectively specified to be M, Cr and C1. When there is a slip between the coordinate origin of two stages, a new vector B is drawn by θ rotation of the rotary stage. The vector B being measurable can be measured to

shift the coordinate origin C1 of stationary stage by one vector A or to shift the coordinate origin Cr of rotary stage by one vector A for calculating the later deviation using the new data thus measured as a new coordinate so that a new deviation due to θ rotation may be prevented from occuring.

COPYRIGHT: (C)1986,JPO&Japio





The Delphion Integrated View

Other Views: INPADOC

Title:

JP61244027A2: CORRECTION OF ORIGIN DEVIATION BETWEEN STATIONARY STAGE AND ROTARY STAGE

Country:

JP Japan

Kind:

Α

Inventor(s):

YAMADA YUICHI **OUTSUKA KAZUHITO**

Applicant/Assignee:

CANON INC

Inquire Regarding Licensing

News, Profiles, Stocks and More about this company

Issued/Filed Dates:

Oct. 30, 1986 / April 22, 1985

Application Number:

JP1985000084583

IPC Class:

H01L 21/30; H01L 21/68; G05B 19/18;


Priority Number(s):

usiness Intelligence Reports

April 22, 1985 JP1985000084583

Abstract:

Purpose: To prevent a new deviation from occurring by correcting θ slip by a method wherein, when there is a deviation between the coordinate origin of rotary stage and the other coordinate origin of stationary stage, the deviation of origin is corrected.



other coordinate origin of stationary stage are

respectively specified to be M, Cr and C1. When there is a slip between the coordinate origin of two stages, a new vector B is drawn by θ rotation of the rotary stage. The vector B being measurable can be measured to shift the coordinate origin C1 of stationary stage by one vector A or to shift the coordinate origin Cr of rotary stage by one vector A for calculating the later deviation using the new data thus measured as a new coordinate so that a new deviation due to θ rotation

may be prevented from occuring. COPYRIGHT: (C)1986,JPO&Japio

Family:

Show known family members

Other Abstract Info:

DERABS C86-328519 DERC86-328519

Foreign References:

No patents reference this one



View <u>image</u>

1 page



Subscribe | Privacy Policy | Terms & Conditions | FAQ | Site Map | Help | Contact Us
© 1997 - 2002 Delphion Inc.